

Description

Fastener Length: 1-", Thread: 1/4-24, Thread Length: 29/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS969812
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-495-3621
Schedule B:	7508.90.5000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS9698-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Minimum And 0.912 Inches Maximum
Fastener Length:	1.000 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.338 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.500 Inches Nominal
Extended Washer Thickness:	0.070 Inches Minimum And 0.080 Inches Maximum
End Item Identification:	F-119
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.088 Inches Minimum And 0.125 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Nickel Alloy Overall
Material Document And Classification:	Ams 5708 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9698-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.