

Description

Fastener Length: 11/16", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS970509
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-141-8183
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS9705-09 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Nominal
Fastener Length:	0.688 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.250 Inches Nominal
Width Between Flats:	0.250 Inches Nominal
Extended Washer Diameter:	0.344 Inches Nominal
Extended Washer Thickness:	0.062 Inches Nominal
Hole Diameter:	0.042 Inches Minimum And 0.052 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.072 Inches Minimum And 0.092 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	175000 Pounds Per Square Inch
Hardness Rating:	34.0 Rockwell C Minimum Overall And 44.0 Rockwell C Maximum Overall
Minimum Yield Strength:	115000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Longitudinal Hole
Material:	Steel Corrosion Resisting Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9705-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.