

Description

Fastener Length: 7/16", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS971405
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-307-0622
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N MS9714-05 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.346 Inches Minimum And 0.366 Inches Maximum
Fastener Length:	0.438 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.258 Inches Nominal
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.040 Inches Minimum And 0.050 Inches Maximum
Hole Diameter:	0.047 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.072 Inches Minimum And 0.092 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Nickel Alloy Overall
Material Document And Classification:	Ams5708 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams2410 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9714-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.