

Description

Fastener Length: 1-", Thread: 1/4-28, Thread Length: 37/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS972408 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-137-8943 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



* See page 2 for technical characteristics

P/N MS9724-08 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.583 Inches Nominal |
| Fastener Length: | 1.012 Inches Nominal |
| Head Style: | Double Hexagon Extended Washer |
| Head Height: | 0.303 Inches Nominal |
| Width Between Flats: | 0.312 Inches Nominal |
| Extended Washer Diameter: | 0.438 Inches Nominal |
| Extended Washer Thickness: | 0.060 Inches Minimum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.429 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 175000 Pounds Per Square Inch |
| Hardness Rating: | 34.0 Rockwell C Minimum Overall And 44.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 115000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Nickel Alloy Overall |
| Material Document And Classification: | Ams 5708 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9724-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.