



Military-Fasteners.com

P/N MS9732-07

Description

Fastener Length: 9/16", Thread: 10-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS973207
Minimum Qty (MOQ):	15 EA
NSN:	5306-01-237-2124
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9732-07 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.460 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.248 Inches Minimum And 0.268 Inches Maximum
Width Between Flats:	0.250 Inches Nominal
Extended Washer Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Extended Washer Thickness:	0.040 Inches Minimum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.072 Inches Minimum And 0.092 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Minimum Yield Strength:	120000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 630 Overall
Material Document And Classification:	Ams5643 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9732-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.