

Description

Fastener Length: 3/4", Thread: 1/4-28, Thread Length: 21/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS973310 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-128-5098 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS9733-10 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.651 Inches Minimum And 0.671 Inches Maximum |
| Fastener Length: | 0.750 Inches Nominal |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.303 Inches Nominal |
| Width Between Flats: | 0.312 Inches Nominal |
| Extended Washer Diameter: | 0.438 Inches Nominal |
| Extended Washer Thickness: | 0.060 Inches Minimum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.079 Inches Minimum And 0.099 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 140000 Pounds Per Square Inch |
| Hardness Rating: | 32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 120000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams5643 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9733-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.