

# P/N MS9750-07

### **Description**

Fastener Length: 1/2", Thread: 10-32, Thread Length: 31/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS975007
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-162-4729
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS9750-07 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.470 Inches Minimum And 0.490 Inches Maximum
Fastener Length:	0.562 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.258 Inches Nominal
Width Between Flats:	0.250 Inches Nominal
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.040 Inches Minimum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.072 Inches Minimum And 0.092 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

### **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/MS9750-07">https://military-fasteners.com/bolts/machine+bolts/MS9750-07</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.