

Description

Hole Diameter: 3/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS976812
Minimum Qty (MOQ):	10
NSN:	5310-00-059-5228
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N MS9768-12 Specifications

Hole Diameter:	0.378 Inches Minimum And 0.388 Inches Maximum
Outside Diameter:	0.865 Inches Minimum And 0.885 Inches Maximum
Recess Diameter:	0.435 Inches Nominal
Material Thickness:	0.107 Inches Minimum And 0.117 Inches Maximum
Hardness Rating:	29.0 Rockwell C Minimum And 39.0 Rockwell C Maximum
Top Recess Diameter:	0.435 Inches Nominal
Bottom Recess Angle:	90.000 Degrees Nominal
Top Recess Angle:	90.000 Degrees Nominal
Bottom Recess Diameter:	0.435 Inches Nominal
Surface Finish:	63.0 Microinches Bottom
Surface Finish:	63.0 Microinches Top
Material Document And Classification:	Ams 5525 Assn Std 1st Material Response Overall Or Ams 5518 Assn Std 2nd Material Response Overall
Style Designator:	Recessed Both Sides

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS9768-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.