

**Description**

Hole Diameter: 3/8",

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS976812
Minimum Qty (MOQ):	10
NSN:	5310-00-059-5228
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE  
AVAILABLE

## P/N MS9768-12 Specifications

<b>Hole Diameter:</b>	0.378 Inches Minimum And 0.388 Inches Maximum
<b>Outside Diameter:</b>	0.865 Inches Minimum And 0.885 Inches Maximum
<b>Recess Diameter:</b>	0.435 Inches Nominal
<b>Material Thickness:</b>	0.107 Inches Minimum And 0.117 Inches Maximum
<b>Hardness Rating:</b>	29.0 Rockwell C Minimum And 39.0 Rockwell C Maximum
<b>Top Recess Diameter:</b>	0.435 Inches Nominal
<b>Bottom Recess Angle:</b>	90.000 Degrees Nominal
<b>Top Recess Angle:</b>	90.000 Degrees Nominal
<b>Bottom Recess Diameter:</b>	0.435 Inches Nominal
<b>Surface Finish:</b>	63.0 Microinches Bottom
<b>Surface Finish:</b>	63.0 Microinches Top
<b>Material Document And Classification:</b>	Ams 5525 Assn Std 1st Material Response Overall Or Ams 5518 Assn Std 2nd Material Response Overall
<b>Style Designator:</b>	Recessed Both Sides

## How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS9768-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.