

## P/N MS9805-07

### **Description**

Fastener Length: 9/16", Thread: 10-32, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS980507
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-198-1697
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS9805-07 Specifications

	_
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.460 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Head Style:	Hexagon
Head Height:	0.115 Inches Minimum And 0.135 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.072 Inches Minimum And 0.092 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Minimum Yield Strength:	120000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Overall
Markarial Danson and Anad Glassifications	Ams5643 Assn Std Single Material Response Overall
Material Document And Classification:	7411350 13 743511 Std Shighe Material Response Overall

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/MS9805-07">https://military-fasteners.com/bolts/machine+bolts/MS9805-07</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.