

Description

Fastener Length: 1/4", Thread: 10-32, Thread Length: 15/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS988503
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-201-1423
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS9885-03 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.220 Inches Minimum And 0.240 Inches Maximum
Fastener Length:	0.312 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.258 Inches Nominal
Width Between Flats:	0.250 Inches Nominal
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.040 Inches Minimum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.072 Inches Minimum And 0.092 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5616 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9885-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.