

P/N MS9886-12

Description

Fastener Length: 7/8", Thread: 1/4-28, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS988612

Minimum Qty (MOQ): 5 EA

NSN: 5306-01-112-3871

Schedule B: 7318.15.8085

ECCN: 9A991



^{*} See page 2 for technical characteristics

P/N MS9886-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.719 Inches Minimum And 0.765 Inches Maximum
Fastener Length:	0.875 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.303 Inches Nominal
Width Between Flats:	0.3125 Inches Nominal
Extended Washer Diameter:	0.458 Inches Nominal
Extended Washer Thickness:	0.080 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.079 Inches Minimum And 0.125 Inches Maximum
Thread Quantity Per Inch:	28
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5616 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9886-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/MS9886-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/MS9886-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/MS9886-12 and selecting the quantity you want then click "add to cart".