

P/N MS9887-13

Description

Fastener Length: 1", Thread: 1/4-24, Thread Length: 59/64", drilled head, MS9887 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS988713
Minimum Qty (MOQ):	5
NSN:	5306-01-021-1846
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS9887-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.874 Inches Minimum And 0.934 Inches Maximum
Fastener Length:	1.062 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.338 Inches Nominal
Width Between Flats:	0.375 Inches Nominal
Extended Washer Diameter:	0.500 Inches Nominal
Extended Washer Thickness:	0.070 Inches Minimum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.128 Inches Minimum And 0.188 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Hardness Rating:	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5616 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9887-13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.