

**Description**

Fastener Length: 7/16", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS989405
Minimum Qty (MOQ):	10 EA
NSN:	5306-00-432-6100
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS9894-05 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.346 Inches Minimum And 0.366 Inches Maximum
<b>Fastener Length:</b>	0.438 Inches Nominal
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.258 Inches Nominal
<b>Width Between Flats:</b>	0.250 Inches Nominal
<b>Extended Washer Diameter:</b>	0.375 Inches Nominal
<b>Extended Washer Thickness:</b>	0.040 Inches Minimum
<b>Hole Diameter:</b>	0.042 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.072 Inches Minimum And 0.092 Inches Maximum
<b>Hole Quantity:</b>	4
<b>Hole Type:</b>	Drilled
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	32.0 Rockwell C Minimum Overall And 38.0 Rockwell C Maximum Overall
<b>Hole Configuration Style:</b>	Hexagon Flats
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams 5616 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9894-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.