

P/N MS9914-05

Description

Fastener Length: 7/16", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS991405

Minimum Qty (MOQ): 10 EA

NSN: 5306-01-032-1111

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS9914-05 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
	0.336 Inches Minimum And 0.376 Inches Maximum
Thread Length:	
Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.248 Inches Minimum And 0.268 Inches Maximum
Width Between Flats:	0.250 Inches Nominal
Extended Washer Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Extended Washer Thickness:	0.040 Inches Minimum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.072 Inches Minimum And 0.092 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9914-05 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.