

P/N MS9914-06

Description

length: 1/2", thread: 10-32, machine bolt - extended washer head - cadmium plated steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| SKU / Model: | MS991406 |
|--------------------|----------|
| Minimum Qty (MOQ): | 10 |

NSN: 5306-00-185-2161

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS9914-06 Specifications

| Thread Class: | 20 |
|--|---|
| | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.388 Inches Minimum And 0.438 Inches Maximum |
| Fastener Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.258 Inches Nominal |
| Width Between Flats: | 0.250 Inches Minimum |
| Extended Washer Diameter: | 0.375 Inches Nominal |
| Extended Washer Thickness: | 0.040 Inches Minimum |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.072 Inches Minimum And 0.092 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Comp 8740 Overall |
| Material Document And Classification: | Ams6322 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Ams2400 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9914-06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.