

Description

Fastener Length: 15/16", Thread: 10-32, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS991413
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-282-1512
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS9914-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.620 Inches Minimum And 0.700 Inches Maximum
Fastener Length:	0.928 Inches Minimum And 0.948 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.248 Inches Minimum And 0.268 Inches Maximum
Width Between Flats:	0.250 Inches Nominal
Extended Washer Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Extended Washer Thickness:	0.040 Inches Minimum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.248 Inches Minimum And 0.308 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9914-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.