



Military-Fasteners.com

P/N MS9914-32

Description

Fastener Length: 2-1/4", Thread: 10-32, Thread Length: 11/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS991432
Minimum Qty (MOQ):	5
NSN:	5306-01-194-2980
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9914-32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.620 Inches Minimum And 0.700 Inches Maximum
Fastener Length:	2.240 Inches Minimum And 2.260 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.248 Inches Minimum And 0.268 Inches Maximum
Width Between Flats:	0.240 Inches Minimum And 0.260 Inches Maximum
Extended Washer Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Extended Washer Thickness:	0.040 Inches Minimum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.560 Inches Minimum And 1.620 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9914-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.