

P/N MS9915-14

Description

Fastener Length: 1-", Thread: 1/4-28, Thread Length: 51/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	M5991514
Minimum Qty (MOQ):	15 EA
NSN:	5306-01-047-0321
Schedule B:	7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS9915-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum And 0.810 Inches Maximum
Fastener Length:	1.000 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.303 Inches Nominal
Width Between Flats:	0.312 Inches Nominal
Extended Washer Diameter:	0.438 Inches Nominal
Extended Washer Thickness:	0.060 Inches Minimum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.190 Inches Minimum And 0.250 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9915-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.