

P/N MS9923-31

Description

Fastener Length: 2-1/8", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 11/16

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS992331
Minimum Qty (MOQ):	1
NSN:	5306-00-341-7001
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS9923-31 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.630 Inches Minimum And 0.690 Inches Maximum
Fastener Length:	2.125 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.258 Inches Nominal
Width Between Flats:	0.250 Inches Nominal
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.040 Inches Minimum
Hole Diameter:	0.042 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.435 Inches Minimum And 1.695 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Round
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9923-31 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.