

Description

Fastener Length: 5/8", Hole Diameter: 1/16", Thread: 1/4-28, Thread Length: 35/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS992408
Minimum Qty (MOQ):	10
NSN:	5306-01-075-1901
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS9924-08 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.516 Inches Minimum And 0.556 Inches Maximum
Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Double Hexagon Extended Washer
Head Height:	0.293 Inches Minimum And 0.313 Inches Maximum
Width Between Flats:	0.302 Inches Minimum And 0.322 Inches Maximum
Extended Washer Diameter:	0.428 Inches Minimum And 0.448 Inches Maximum
Extended Washer Thickness:	0.060 Inches Nominal
Hole Diameter:	0.060 Inches Minimum And 0.070 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.079 Inches Minimum And 0.099 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9924-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.