

## P/N MS9924-17

### **Description**

Fastener Length: 1-3/16", Hole Diameter: 1/16", Thread: 1/4-28, Thread Length: 13/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS992417
Minimum Qty (MOQ):	15 EA
NSN:	5306-01-107-4144
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS9924-17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.740 Inches Minimum And 0.820 Inches Maximum
Fastener Length:	1.178 Inches Minimum And 1.198 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.293 Inches Minimum And 0.313 Inches Maximum
Width Between Flats:	0.302 Inches Minimum And 0.322 Inches Maximum
Extended Washer Diameter:	0.428 Inches Minimum And 0.448 Inches Maximum
Extended Washer Thickness:	0.060 Inches Minimum
Hole Diameter:	0.065 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.378 Inches Minimum And 0.438 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

