

Description

Fastener Length: 11/16", Hole Diameter: 1/16", Thread: 1/4-28, Thread Length: 9/16", drilled, MS9958 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS995809
Minimum Qty (MOQ):	5
NSN:	5306-01-078-8927
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9958-09 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.589 Inches Nominal
Fastener Length:	0.688 Inches Nominal
Head Style:	Hexagon
Head Height:	0.250 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Primary Washer
Surface Finish:	32.0 Microinches Threads
Material:	Steel Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9958-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.