

## P/N N5000-56H

### **Description**

N5000 series ring

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: N500056H

Minimum Qty (MOQ): 10

NSN: 5325-00-807-5331

Schedule B: 7318.29.0000

ECCN: N/A

National Motor Freight: 095190, Hardware, Noi Sub 9









<sup>\*</sup> See page 2 for technical characteristics

# P/N N5000-56H Specifications

Cross-sectional Shape Style:	Rectangular
Casehardening Indicator:	Not Casehardened
Outside Diameter:	0.615 Inches Minimum And 0.630 Inches Maximum
Major Thickness:	0.033 Inches Minimum And 0.037 Inches Maximum
Ring Style:	Internal
Usage Design:	Internal
Material Hardness Rating:	63.0 Rockwell Superficial 30-n Minimum And 69.5 Rockwell Superficial 30-n Maximum
Material:	Steel, Ams 5520
Material:	Steel Comp 632
Material Document And Classification:	Ams 5520 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated, Qq-p-35

# **How to Order**

Order this retaining ring from our inventory online by visiting <a href="https://military-fasteners.com/rings/retaining+rings/N5000-56H">https://military-fasteners.com/rings/retaining+rings/N5000-56H</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/N5000-56H">https://military-fasteners.com/rings/retaining+rings/N5000-56H</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/retaining+rings/N5000-56H">https://military-fasteners.com/rings/retaining+rings/N5000-56H</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rings/n5000-56H">https://military-fasteners.com/rings/n5000-56H</a> and selecting the quantity you want <a href="https://military-fasteners.com/rings/n5000-56H">https://military-fasteners.com/rings/n5000-56H</a> and selecting the property of the property