

P/N NA0036-050018

Description

NA0036-050018 Close Tolerance Bolt

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NA0036050018
Minimum Qty (MOQ):	5
NSN:	5306-01-147-4037
Schedule B:	7318.15.2000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NA0036-050018 Specifications

Thread Direction:	Right-hand
Thread Length:	8.5 Millimeters Minimum And 9.5 Millimeters Maximum
Fastener Length:	26.70 Millimeters Minimum And 27.30 Millimeters Maximum
Head Style:	Undercut Hexagon
Head Height:	2.7 Millimeters Minimum And 3.0 Millimeters Maximum
Width Between Flats:	7.85 Millimeters Minimum And 8.00 Millimeters Maximum
Grip Diameter:	4.9650 Millimeters Minimum And 4.9900 Millimeters Maximum
Nominal Thread Diameter:	5.0 Millimeters
Grip Length:	17.80 Millimeters Minimum And 18.20 Millimeters Maximum
Minimum Tensile Strength:	1100 Megapascals
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Thread Pitch In Millimeters:	0.8
Surface Finish:	0.8 Micrometers Bearing Surface Of Head
Surface Finish:	0.8 Micrometers Grip
Surface Finish:	0.8 Micrometers Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Mj
Specification/standard Data:	80205-na0036 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NA0036-050018 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.