

Description

NA0036-060008 Close Tolerance Bolt

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NA0036060008
Minimum Qty (MOQ):	10
NSN:	5306-01-113-9770
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

P/N NA0036-060008 Specifications

Thread Direction:	Right-hand
Thread Length:	9.5 Millimeters Minimum And 10.5 Millimeters Maximum
Fastener Length:	17.70 Millimeters Minimum And 18.30 Millimeters Maximum
Head Style:	Undercut Hexagon
Head Height:	3.2 Millimeters Minimum And 3.5 Millimeters Maximum
Width Between Flats:	9.78 Millimeters Minimum And 10.00 Millimeters Maximum
Grip Diameter:	5.9650 Millimeters Minimum And 5.9900 Millimeters Maximum
Nominal Thread Diameter:	6.0 Millimeters
Grip Length:	7.80 Millimeters Minimum And 8.20 Millimeters Maximum
Minimum Tensile Strength:	1100 Megapascals
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Thread Pitch In Millimeters:	1.0
Surface Finish:	0.8 Micrometers Bearing Surface Of Head
Surface Finish:	0.8 Micrometers Grip
Surface Finish:	0.8 Micrometers Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Mj
Specification/standard Data:	80205-na0036 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NA0036-060008> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.