

P/N NA0069A040010

Description

NA0069A040010 Socket Head Cap Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NA0069A040010

Minimum Qty (MOQ): 25

NSN: 5305-01-612-9294

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N NA0069A040010 Specifications

Thread Direction:	Right-hand
Thread Length:	9.7 Millimeters Minimum And 10.3 Millimeters Maximum
Fastener Length:	9.7 Millimeters Minimum And 10.3 Millimeters Maximum
Head Style:	Flat Chamfer
Head Diameter:	6.80 Millimeters Minimum And 7.00 Millimeters Maximum
Head Height:	3.88 Millimeters Minimum And 4.00 Millimeters Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	4.0 Millimeters
Width Across Flats:	3.020 Millimeters Minimum And 3.071 Millimeters Maximum
Minimum Tensile Strength:	8720 Newtons Per Square Millimeter
Thread Pitch In Millimeters:	0.7
Part Name Assigned By Controlling Agency:	Screws, Cap, Hexagon Socket Head, Full Thread A-286, 1100mpa, Metric
Material:	Iron Alloy 660 Or Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Or Ams5732 Assn Std 1st Material Response Or Ams5737 Assn Std 1st Material Response Or Ams5853 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Ams2700, Method 1, Class 4 Assn Std Single Treatment Response Overall
Thread Series Designator:	Mj

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NA0069A040010 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.