

Description

NA0069A040010 Socket Head Cap Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NA0069A040010
Minimum Qty (MOQ):	25
NSN:	5305-01-612-9294
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N NA0069A040010 Specifications

Thread Direction:	Right-hand
Thread Length:	9.7 Millimeters Minimum And 10.3 Millimeters Maximum
Fastener Length:	9.7 Millimeters Minimum And 10.3 Millimeters Maximum
Head Style:	Flat Chamfer
Head Diameter:	6.80 Millimeters Minimum And 7.00 Millimeters Maximum
Head Height:	3.88 Millimeters Minimum And 4.00 Millimeters Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	4.0 Millimeters
Width Across Flats:	3.020 Millimeters Minimum And 3.071 Millimeters Maximum
Minimum Tensile Strength:	8720 Newtons Per Square Millimeter
Thread Pitch In Millimeters:	0.7
Part Name Assigned By Controlling Agency:	Screws, Cap, Hexagon Socket Head, Full Thread A-286, 1100mpa, Metric
Material:	Iron Alloy 660 Or Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Or Ams5732 Assn Std 1st Material Response Or Ams5737 Assn Std 1st Material Response Or Ams5853 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Ams2700, Method 1, Class 4 Assn Std Single Treatment Response Overall
Thread Series Designator:	Mj

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NA0069A040010> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.