

Description

Fastener Length: 1-15/64", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 1/2", NAS1003 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS100312H |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-240-7382 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1003-12H Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.451 Inches Minimum And 0.511 Inches Maximum |
| Fastener Length: | 1.216 Inches Minimum And 1.246 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.109 Inches Minimum And 0.141 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Hole Diameter: | 0.046 Inches Minimum And 0.056 Inches Maximum |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.735 Inches Minimum And 0.765 Inches Maximum |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 140000 Pounds Per Square Inch |
| Hole Configuration Style: | Hexagon Flats |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1003 Professional/industrial Association Standard |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1003-12H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.