

Description

Fastener Length: 1-9/32", Thread: 10-32, Thread Length: 15/32", NAS1003 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS100313A |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-680-6547 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1003-13A Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.481 Inches Minimum |
| Fastener Length: | 1.293 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.125 Inches Nominal |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.812 Inches Nominal |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 140000 Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5732 Assn Std 1st Material Response Overall Or Ams 5737 Assn Std 1st Material Response Overall Or Ams 5733 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Special Test Features: | Tensile Strength At Room Temperature |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1003-13A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.