Military-Fasteners.com

# P/N NAS1003-2

**Description**

length: 0.606", thread: 10-32, hex head, drilled shank, corrosion resistant steel, NAS1003 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

| | |
|---|---|
| SKU / Model: | NAS10032 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5306-00-827-2275 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

* See page 2 for technical characteristics

# P/N NAS1003-2 Specifications

| | |
|---|---|
| **Thread Class:** | 3a |
| **Thread Direction:** | Right-hand |
| **Thread Length:** | 0.481 Inches Minimum |
| **Fastener Length:** | 0.606 Inches Nominal |
| **Head Style:** | Hexagon |
| **Head Height:** | 0.125 Inches Nominal |
| **Width Between Flats:** | 0.367 Inches Minimum And 0.376 Inches Maximum |
| **Shank Unthreaded Hole Diameter:** | 0.070 Inches Nominal First Hole |
| **Nominal Thread Diameter:** | 0.190 Inches |
| **Grip Length:** | 0.125 Inches Nominal |
| **Features Provided:** | Finished Head |
| **Thread Quantity Per Inch:** | 32 |
| **Minimum Tensile Strength:** | 140000 Pounds Per Square Inch |
| **Distance From Head Largest Bearing Surface To Shank Hole Center:** | 0.391 Inches Nominal First Hole |
| **Special Features:** | Tensile Strength At Room Temperature |
| **Material:** | Iron Alloy 660 Overall |
| **Material Document And Classification:** | Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| **Surface Treatment:** | Passivate Overall |
| **Surface Treatment Document And Classification:** | Mil-s-5002 Mil Spec Single Treatment Response Overall |
| **Thread Series Designator:** | Unf |

## How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS1003-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.