

P/N NAS1003-20A

Description

Fastener Length: 1-23/32", Thread: 10-32, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS100320A

Minimum Qty (MOQ): 5 EA

NSN: 5306-00-828-7776

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1003-20A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.481 Inches Minimum
Fastener Length:	1.731 Inches Nominal
Head Style:	Hexagon
Head Height:	0.125 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.250 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Special Features:	Tensile Strength At Room Temperature
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5732 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS1003-20A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS1003-20A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS1003-20A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS1003-20A and selecting the quantity you want then click "add to cart".