



Military-Fasteners.com

P/N NAS1003-20H

Description

Fastener Length: 1-47/64", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS100320H
Minimum Qty (MOQ):	10 EA
NSN:	5306-00-997-5906
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1003-20H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.481 Inches Maximum
Fastener Length:	1.716 Inches Minimum And 1.746 Inches Maximum
Head Style:	Hexagon
Head Height:	0.107 Inches Minimum And 0.139 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.235 Inches Minimum And 1.265 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Casehardened And Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Longitudinal Hole
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1003-20H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.