

P/N NAS1003-20H

Description

Fastener Length: 1-47/64", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS100320H

Minimum Qty (MOQ): 10 EA

NSN: 5306-00-997-5906

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1003-20H Specifications

| Thread Class: | 3a |
|---------------------------|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.481 Inches Maximum |
| Fastener Length: | 1.716 Inches Minimum And 1.746 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.107 Inches Minimum And 0.139 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Hole Diameter: | 0.046 Inches Nominal |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 1.235 Inches Minimum And 1.265 Inches Maximum |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Features Provided: | Casehardened And Finished Head |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 140000 Pounds Per Square Inch |
| Hole Configuration Style: | Hexagon Longitudinal Hole |
| Material: | Iron Alloy 660 Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS1003-20H and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.