

Description

Thread: 10-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS100323A
Minimum Qty (MOQ):	10 EA
NSN:	5306-00-997-5905
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1003-23A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.441 Inches Minimum And 0.511 Inches Maximum
Fastener Length:	1.904 Inches Minimum And 1.934 Inches Maximum
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.423 Inches Minimum And 1.453 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Navy Special Project
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1003 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1003-23A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.