

**Description**

Fastener Length: 43/64", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS10033H                                 |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-754-2082                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1003-3H Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.451 Inches Minimum And 0.511 Inches Maximum                                     |
| <b>Fastener Length:</b>                               | 0.654 Inches Minimum And 0.684 Inches Maximum                                     |
| <b>Head Style:</b>                                    | Hexagon   |
| <b>Head Height:</b>                                   | 0.109 Inches Minimum And 0.141 Inches Maximum                                     |
| <b>Width Between Flats:</b>                           | 0.367 Inches Minimum And 0.376 Inches Maximum                                     |
| <b>Hole Diameter:</b>                                 | 0.046 Inches Nominal  |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Grip Length:</b>                                   | 0.173 Inches Minimum And 0.203 Inches Maximum                                     |
| <b>Hole Quantity:</b>                                 | 1   |
| <b>Hole Type:</b>                                     | Drilled   |
| <b>Features Provided:</b>                             | Finished Head   |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 140000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall |
| <b>Hole Configuration Style:</b>                      | Hexagon Flats   |
| <b>Material:</b>                                      | Iron Alloy 660 Overall  |
| <b>Material Document And Classification:</b>          | Ams 5732 Assn Std Single Material Response Overall                                |
| <b>Surface Treatment:</b>                             | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-s-5002 Mil Spec Single Treatment Response Overall                             |
| <b>Thread Series Designator:</b>                      | Unf   |
| <b>Specification/standard Data:</b>                   | 80205-nas1003 Professional/Industrial Association Standard                        |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1003-3H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.