

**Description**

Fastener Length: 3-7/64", Thread: 10-32, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS100342A                                |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-00-182-9471                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1003-42A Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.451 Inches Minimum And 0.511 Inches Maximum   |
| <b>Fastener Length:</b>                               | 3.091 Inches Minimum And 3.121 Inches Maximum   |
| <b>Head Style:</b>                                    | Hexagon   |
| <b>Head Height:</b>                                   | 0.109 Inches Minimum And 0.141 Inches Maximum   |
| <b>Width Between Flats:</b>                           | 0.367 Inches Minimum And 0.376 Inches Maximum   |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Grip Length:</b>                                   | 2.610 Inches Minimum And 2.640 Inches Maximum   |
| <b>Features Provided:</b>                             | Finished Head   |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Hardness Rating:</b>                               | 248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall   |
| <b>Material Document And Classification:</b>          | Ams 5732 Assn Std 1st Material Response Overall Or Ams 5737 Assn Std 1st Material Response Overall Or Ams 5733 Assn Std 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-s-5002 Mil Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unf   |
| <b>Specification/standard Data:</b>                   | 80205-nas1003 Professional/industrial Association Standard  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1003-42A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.