

Description

Fastener Length: 55/64", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS10036H
Minimum Qty (MOQ):	5
NSN:	5306-00-057-0213
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1003-6H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.451 Inches Minimum And 0.511 Inches Maximum
Fastener Length:	0.841 Inches Minimum And 0.871 Inches Maximum
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:	0.051 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.360 Inches Minimum And 0.390 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Flats
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5732 Assn Std 1st Material Response Overall Or Ams5737 Assn Std 1st Material Response Overall Or Ams5733 Assn Std 3rd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1003 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1003-6H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.