

Description

Fastener Length: 29/32", Thread: 10-32, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS10037
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-916-6490
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1003-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.481 Inches Minimum
Fastener Length:	0.919 Inches Nominal
Head Style:	Hexagon
Head Height:	0.125 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Nominal First Hole
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.438 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.704 Inches Nominal First Hole
Special Features:	Tensile Strength At Room Temperature
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1003-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.