

Description

Thread: 10-32, Thread Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS10039A                                 |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5306-00-543-5044                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1003-9A Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.451 Inches Minimum And 0.511 Inches Maximum  |
| <b>Fastener Length:</b>                               | 1.028 Inches Minimum And 1.058 Inches Maximum  |
| <b>Head Style:</b>                                    | Hexagon  |
| <b>Head Height:</b>                                   | 0.109 Inches Minimum And 0.141 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.367 Inches Minimum And 0.376 Inches Maximum  |
| <b>End Item Identification:</b>                       | Arleigh Burke Class Ddg;phalanx;deep Submergence Systems;forestal Class Cv;f-16 Aircraft;485I Tacs;seasprite Helicopter;f/a-18 Hornet;f-16 Simulator;b-1b Bomber |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Grip Length:</b>                                   | 0.547 Inches Minimum And 0.577 Inches Maximum  |
| <b>Features Provided:</b>                             | Finished Head  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 140000 Pounds Per Square Inch  |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams 5733 Assn Std 1st Material Response Overall Or Ams 5735 Assn Std 2nd Material Response Overall Or Ams 5737 Assn Std 2nd Material Response Overall            |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-s-5002 Mil Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unf  |
| <b>Specification/standard Data:</b>                   | 80205-nas1003 Professional/Industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1003-9A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.