

Description

Fastener Length: 1-5/32", Thread: 1/4-28, Thread Length: 17/32",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS100410A
Minimum Qty (MOQ):	5
NSN:	5306-00-682-5606
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1004-10A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.544 Inches Minimum
Fastener Length:	1.169 Inches Nominal
Head Style:	Hexagon
Head Height:	0.156 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.625 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Special Test Features:	Tensile Strength At Room Temperature
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1004-10A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.