

**Description**

Fastener Length: 1-27/64", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 9/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS100414H
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-485-2269
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1004-14H Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.514 Inches Minimum And 0.574 Inches Maximum
<b>Fastener Length:</b>	1.404 Inches Minimum And 1.434 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.140 Inches Minimum And 0.172 Inches Maximum
<b>Width Between Flats:</b>	0.430 Inches Minimum And 0.439 Inches Maximum
<b>Hole Diameter:</b>	0.046 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.860 Inches Minimum And 0.890 Inches Maximum
<b>Hole Quantity:</b>	1
<b>Hole Type:</b>	Drilled
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	130000 Pounds Per Square Inch
<b>Hardness Rating:</b>	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
<b>Minimum Yield Strength:</b>	85000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Hexagon Flats
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall Or Ams5732 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-s-5002 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1004-14H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.