

Description

Fastener Length: 1-17/32", Thread: 1/4-28, Thread Length: 17/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS100416
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-917-9774
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1004-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.544 Inches Minimum
Fastener Length:	1.544 Inches Nominal
Head Style:	Hexagon
Head Height:	0.156 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.000 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.312 Inches Nominal First Hole
Special Features:	Tensile Strength At Room Temperature
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1004-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.