

Description

Fastener Length: 23/32", Thread: 1/4-28, Thread Length: 17/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS10043
Minimum Qty (MOQ):	10
NSN:	5306-00-857-4431
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1004-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.544 Inches Minimum
Fastener Length:	0.732 Inches Nominal
Head Style:	Hexagon
Head Height:	0.156 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.188 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.500 Inches Nominal First Hole
Special Features:	Tensile Strength At Room Temperature
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5732 Assn Std Single Material Response Overall And Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1004-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.