

P/N NAS1004-30A

Military-Fasteners.com

Description

Fastener Length: 2-27/64", Thread: 1/4-28, Thread Length: 9/16", NAS1004 series bolt

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

| SKU / Model: | NAS100430A |
|-------------------------|---|
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-001-9764 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1004-30A Specifications

| Thread Class: | За |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.514 Inches Minimum And 0.574 Inches Maximum |
| Fastener Length: | 2.404 Inches Minimum And 2.434 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.140 Inches Minimum And 0.172 Inches Maximum |
| Width Between Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 1.860 Inches Minimum And 1.890 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 140000 Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas1004 Professional/industrial Association Standard |

How to Order

Order this machine bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/NAS1004-30A</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.