

Description

Fastener Length: 2-21/32", Thread: 1/4-28, Thread Length: 17/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS100434A
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-820-8109
National Motor Freight:	013280, Alum Bolts



* See page 2 for technical characteristics

P/N NAS1004-34A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.544 Inches Minimum
Fastener Length:	2.669 Inches Nominal
Head Style:	Hexagon
Head Height:	0.156 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.125 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Special Features:	Tensile Strength At Room Temperature
Material:	Iron Alloy 660 Overall Or Steel Comp 630 Overall
Material Document And Classification:	Ams 5732 Assn Std 1st Material Response Overall Or Ams 5737 Assn Std 1st Material Response Overall Or Ams 5733 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1004-34A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.