

Description

Fastener Length: 1-1/32", Hole Diameter: ", Thread: 1/4-28, Thread Length: 17/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS10048H
Minimum Qty (MOQ):	5
NSN:	5306-00-062-0822
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1004-8H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.544 Inches Minimum
Fastener Length:	1.044 Inches Nominal
Head Style:	Hexagon
Head Height:	0.156 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Hole Diameter:	0.062 Inches Nominal
End Item Identification:	W/s: 485I Tacs; Aircraft, Orion P-3; Aircraft, Thunderbolt II, A-10; Deep Submergence Systems Programs (dssp); Tactical Air Opns Module (an/tyq-(23); Aircraft, T-37; Aircraft, T-38; Aircraft, Freedom Fighter F-5; Aircraft, Starlifter C-141; Aircraft, Galaxy C-5
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.485 Inches Minimum And 0.515 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Yield Strength:	85000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Flats
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1004 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1004-8H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.