

Description

Fastener Length: 1-7/64", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 9/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS10049A
Minimum Qty (MOQ):	10
NSN:	5306-01-037-6046
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1004-9A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.514 Inches Minimum And 0.574 Inches Maximum
Fastener Length:	1.091 Inches Minimum And 1.121 Inches Maximum
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.547 Inches Minimum And 0.577 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Flats
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1004 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1004-9A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.