

Description

Fastener Length: 45/64", Thread: 1/4-24, Thread Length: 21/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS10051
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-172-5538
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1005-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.607 Inches Minimum And 0.657 Inches Maximum
Fastener Length:	0.679 Inches Minimum And 0.709 Inches Maximum
Head Style:	Hexagon
Head Height:	0.172 Inches Minimum And 0.204 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.501 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.052 Inches Minimum And 0.072 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.411 Inches Minimum First Hole And 0.431 Inches Maximum First Hole
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1005 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1005-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.