

**Description**

Fastener Length: 1-1/16", Thread: 1/4-24, Thread Length: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS10057A
Minimum Qty (MOQ):	2
NSN:	5306-00-854-5804
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1005-7A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.632 Inches Minimum
<b>Fastener Length:</b>	1.070 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.188 Inches Nominal
<b>Width Between Flats:</b>	0.492 Inches Minimum And 0.501 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	0.438 Inches Nominal
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	140000 Pounds Per Square Inch
<b>Special Features:</b>	Tensile Strength At Room Temperature
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-s-5002 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1005-7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.